



Performance – Winter
General Purpose

Ranger Ice

Ranger Ice		specification				
Size	Service Index	Rec Rim	Section Width (mm)	Overall Dia (mm)	Static Loaded Radius (mm)	Rim Range (inch)
50						
255/50R19 XL	107V	8.0	265	739	338	7.0 - 9.0
55						
235/55R17	99H	7.5	245	690	317	6.5 - 8.5
255/55R18 XL	109V	8.0	265	737	338	7.0 - 9.0
60						
235/60R18* XL	107H	7.0	240	739	338	6.5 - 8.5
65						
215/65R16	98H	6.5	221	686	312	6.0 - 7.5
235/65R17 XL	108H	7.0	240	738	335	6.5 - 8.5
265/65R17	112H	8.0	272	776	350	7.5 - 9.5
70						
205/70R15	96T	6.0	209	669	303	5.0 - 7.0
215/70R16	100T	6.5	221	708	321	5.5 - 7.0

XL - Extra Load or Reinforced.
* - Limited availability.

Winter tyre for 4x4s

- Excellent traction in deep snow, ice, slush, mud and plain wet surfaces
- Strong resistance to aquaplaning through standing water
- Keen handling characteristics
- Good road holding in the dry and wet
- Some versions speed rated to 130mph to suit modern, high performance 4x4s
- Marked with 'Severe Snow Conditions' symbol

