

Classic

Speedmaster (AM6)

Speed rated to 112mph/180kmh, the Speedmaster MKII has the curved tread profile and ribbed pattern so typical of classic bikes. And though it handles like a true classic, you can also look forward to the enhanced durability and performance modern rubber compounds afford. Best used in conjunction with the Safety Mileage MKII.



Speedmaster



Sidecar Triple Duty Universal

Classic

Safety Mileage MKII (AM7)

When you've a Speedmaster up-front, the Safety Mileage MKII is what you need on the back. Available in a variety of different tread patterns all sharing performance characteristics in tune with older bikes, while enjoying cutting-edge advances made in rubber technology.



Safety Mileage MKII



Safety Mileage MKII (4.00-19)



Safety Mileage MKII (5.00-16)

Classic

Sidecar Triple Duty Universal

Although especially suited to the front wheel, these tyres can be used in any position on a sidecar outfit.

AM6/AM7 / Sidecar Triple specification

Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
Speedmaster AM6								
1727410	300-19 TT*	54S	1.85	1.60 - 2.15	78 / 3.1	641 / 25.2	3.5	517 / 827.2
1658410	300-20 TT*	50S	1.85	1.60 - 2.15	75 / 3.0	665 / 26.2	3.5	498 / 796.7
1659401	300-21 TT*	57S	1.85	1.60 - 2.15	76 / 3.0	691 / 27.2	3.6	481 / 769.6
1657501	325-19 TT	54S	2.15	1.85 - 2.50	86 / 3.4	658 / 25.9	4.0	497 / 795.2
1657601	350-19 TT	57S	2.15	1.85 - 2.50	92 / 3.6	682 / 26.9	3.6	482 / 771.2
1655501	3.25-17 TT	50S	2.15	1.85 - 2.50	89 / 3.5	616 / 24.3	3.5	538 / 860.1

Safety Mileage MK II AM7								
1727610	350-19 TT	57S	2.15	1.85 - 2.50	93 / 3.7	682 / 26.9	8.1	482 / 771.2
1646801	400-18 TT	64S	2.50	2.15 - 3.00	111 / 4.4	677 / 26.7	8.1	488 / 780.8
1647801	400-19 TT	65S	2.50	2.15 - 3.00	110 / 4.3	702 / 27.6	9.2	471 / 753.6
1694901	500-16 TT	69S	3.00D	3.00 - 3.50	131 / 5.2	669 / 26.3	8.1	499 / 798.4
1645501	3.25-17 TT	50S	2.15	1.85 - 2.50	89 / 3.5	616 / 24.3	3.5	538 / 860.1

Sidecar Triple Duty								
1697605	350-19 TT	57L	2.15	1.85 - 2.50	92 / 3.6	679 / 26.7	9.4	491 / 785.6

TT - Tube Type. * Reinforced.