

General Purpose

Avanza AV9, AV4 & Supervan

Modern high speed van tyres

- Long tyre life
- Robust sidewalls to cope with kerbing damage
- Excellent value
- Reinforced to handle heavy loads
- First-rate wet weather performance
- Available with a speed rating of up to 118mph



AV9

AV4

Supervan

Avanza AV9 specification

Size	Service Index	Rec Rim	Section Width (mm)	Overall Dia (mm)	Static Loaded Radius (mm)	Rim Range (Inch)
65						
205/65R15 C	102/100T	6.0	209	647	297	5.5 - 6.5
215/65R15 C	104/102T	6.5	221	661	303	6.0 - 7.0
195/65R16 C	104/102R	6.0	201	660	305	5.5 - 6.0
205/65R16 C	107/105R	6.0	209	672	309	5.5 - 6.5
225/65R16 C	112/110R	6.5	228	698	320	6.0 - 7.0
235/65R16 C	115/113R	7.0	240	712	325	6.5 - 7.5
70						
195/70R15 C	104/102R (97T)	6.0	201	655	300	5.0 - 6.0
215/70R15 C	109/107R	6.5	221	683	311	5.5 - 7.0
225/70R15 C	112/110R (115N)	6.5	228	697	317	6.0 - 7.0
75						
175/75R16 C	101/99R (104N)	5.0	177	668	308	4.5 - 5.5
185/75R16 C	104/102R	5.0	184	684	314	5.0 - 6.0
195/75R16 C	107/105R	5.5	196	698	320	5.0 - 6.0
205/75R16 C	113/111R	5.5	203	714	326	5.5 - 6.5
215/75R16 C	116/114R	6.0	216	728	332	6.5 - 7.0
225/75R16 C	121/120R	6.0	223	744	338	6.0 - 7.0

XL - Extra Load or Reinforced.

AV4 specification

Size	Service Index	Rec Rim	Section Width (mm)	Overall Dia (mm)	Static Loaded Radius (mm)	Rim Range (Inch)
82						
185R14 C	102P	5.5	188	650	296	5.0 - 6.0
195R14 C	106N	5.5	198	666	302	5.0 - 6.0
185R15 C	103P	5.5	188	674	308	5.0 - 6.0

Supervan specification

Size	Service Index	Rec Rim	Section Width (mm)	Overall Dia (mm)	Static Loaded Radius (mm)	Rim Range (Inch)
82						
175R13 C	94/92N	5.0	178	608	276	4.5 - 5.5

