



Cruiser/Touring/Custom

Cobra

- Aimed at the power cruiser/touring/custom market
- Incorporates sports tyre technology for nimble handling
- Incredible stability and longevity – perfect for touring
- Extra wide sizes for custom bikes



Cobra specification

Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
Cobra AV71 Front								
4710018	MH90-21	56V	MT1.85	1.60 - 2.15	83 / 3.3	688 / 27.1	5.2	479 / 766.4
4710013	120/70ZR19 (60W)		MT3.50	3.00 - 3.75	123 / 4.8	649 / 25.6	4.7	523 / 836.8
4710015	120/70-21	62V	MT3.50	2.75 - 3.75	120 / 4.7	709 / 27.9	4.8	467 / 747.3
4710019	130/80B17	65H	MT3.00	2.50 - 3.50	129 / 5.1	654 / 25.7	4.8	492 / 787.2
4710012	130/70R18	63H	MT3.50	3.50 - 4.00	128 / 5.0	647 / 25.5	4.7	517 / 827.2
4710010	150/80R16	71V	MT3.50	3.50 - 4.25	149 / 5.9	647 / 25.5	4.7	517 / 827.2
4710011	150/80R17	72H	MT3.50	3.50 - 4.25	150 / 5.9	672 / 26.5	4.7	496 / 793.6
4710016	150/80R17 (72V)		MT3.50	3.50 - 4.25	150 / 5.9	672 / 26.5	4.7	496 / 793.6

Cobra AV71 Universal								
4710014	130/60R23	65V	MT3.50	3.50 - 4.00	124 / 4.9	744 / 29.3	4.8	442 / 707.2

Cobra AV72 Rear								
4700011	180/60R16	74H	MT5.00	5.00 - 5.50	182 / 7.2	630 / 24.8	8.4	522 / 835.2
4710022	180/65B16	81H	MT5.00	4.25 - 5.50	180 / 7.1	640 / 25.2	8.3	515 / 824.0
4700010	180/70R16	77H	MT5.00	5.00 - 5.50	182 / 7.2	656 / 25.8	8.5	510 / 816.0
4700014	180/55ZR18 (74W)		MT5.50	5.50 - 6.00	184 / 7.2	655 / 25.8	6.6	514 / 822.4
4700012	200/60R16	79V	MT5.50	5.50 - 6.25	196 / 7.7	649 / 25.6	7.0	519 / 830.4
4700013	200/55R17	78V	MT6.25	6.00 - 6.50	198 / 7.8	658 / 25.9	6.8	513 / 820.8
4700015	200/55R18	79V	MT6.25	6.00 - 6.50	198 / 7.8	679 / 26.7	6.8	488 / 780.3
4700020	220/50R20	83V	MT7.00	6.50 - 7.50	221 / 8.7	728 / 28.7	6.8	453 / 724.8
4700021	240/50R16	84V	MT7.50	7.00 - 8.00	238 / 9.4	650 / 25.6	7.2	509 / 814.4
4700019	240/40VR18 (79V)		MT8.50	8.00 - 9.00	238 / 9.4	648 / 25.5	9.2	509 / 814.4
4700016	250/40VR18 (81V)		MT9.00	8.50 - 9.50	251 / 9.9	655 / 25.8	6.6	514 / 822.4
4700018	280/40VR20 (89V)		MT10.0	9.50 - 10.50	281 / 11.1	732 / 28.8	6.5	458 / 732.8
4700017	300/35VR18 (87V)		MT10.5	10.00 - 11.00	300 / 11.8	664 / 26.1	6.5	497 / 795.2

