

Street Bias

Roadrider

- Comprehensive range of sizes – from modern to more traditional
- Large contact patch for excellent grip at all lean angles
- Performance upgrade for classic and vintage motorcycles
- Intermittent centre groove for straight line stability



Roadrider specification

Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/ inches	Overall Diameter mm/ inches	Depth mm	Revs per km/mile
Roadrider AM26 Front								
2269913	90/90-18	51V	2.15	1.85 - 2.50	97 / 3.8	619 / 24.4	5	535 / 855.9
2268813	90/90-19	52V	2.15	1.85 - 2.50	99 / 3.9	647 / 25.5	5	512 / 818.9
2268113	90/90-21*	54V	2.15	1.85 - 2.50	98 / 3.9	698 / 27.5	5	474 / 759.0
2268313	100/90-16	54V	2.50	2.15 - 2.75	106 / 4.2	588 / 23.1	5	563 / 901.0
2268213	110/90-16	59V	MT2.50	2.15 - 3.00	117 / 4.6	603 / 23.7	5	549 / 878.6
2260213	100/80-17	52V	MT2.50	2.15 - 2.75	101 / 4.0	595 / 23.4	5	557 / 890.4
2265213	110/70-17	54V	MT3.00	2.50 - 3.50	108 / 4.3	593 / 23.3	5	558 / 893.4
2265513	110/80-17	57V	MT2.5	2.15 - 3.00	112 / 4.4	614 / 24.2	5	539 / 862.9
2266113	120/70-17	58V	MT3.5	2.75 - 3.75	120 / 4.7	607 / 23.9	5	546 / 872.8

Roadrider AM26 Rear

2276813	4.00-18	64V	MT2.50	2.15 - 3.00	116 / 4.6	671 / 26.4	7.5	493 / 789.6
2279513	120/80-18	62V	MT2.75	2.50 - 3.00	120 / 4.7	652 / 25.7	7.5	508 / 812.6
2276013	120/90-18	65V	MT2.75	2.50 - 3.00	130 / 5.1	675 / 26.6	7.5	491 / 784.9
2279813	130/80-18	66V	MT2.75	2.50 - 3.50	137 / 5.4	672 / 26.5	7.5	493 / 788.4
2275713	130/90-17	68V	MT3.50	2.50 - 3.50	140 / 5.5	671 / 26.4	7.5	493 / 789.6
2276613	130/70-18	63V	MT3.50	3.00 - 4.00	133 / 5.2	649 / 25.6	7.5	510 / 816.3
2279713	140/70-18	67V	MT3.75	3.50 - 4.50	142 / 5.6	666 / 26.2	7.5	497 / 795.5
2277413	150/80-16	71V	MT3.50	3.00 - 4.25	161 / 6.3	655 / 25.8	7.5	506 / 808.9
2275113	150/70-17	69V	MT4.00	3.50 - 4.50	156 / 6.1	656 / 25.8	7.5	505 / 807.6
2275913	130/80-17	65V	MT3.00	2.50 - 3.50	136 / 5.4	645 / 25.4	7.5	513 / 821.4
2279913	130/70-17	62V	MT3.50	3.00 - 4.00	130 / 5.1	625 / 24.6	7.5	530 / 847.7
2277613	140/70-17	66V	MT3.75	3.50 - 4.50	140 / 5.5	641 / 25.2	7.5	517 / 826.5
2276513	150/70-18	70V	MT4.25	3.50 - 4.50	154 / 6.1	658 / 25.9	7.5	503 / 805.2
2270313	MT90-16*	74V	3.00D	2.50 - 3.50	137 / 5.4	646 / 24.4	7.5	514 / 822.7

Roadrider AM26 Universal

2267513	3.25-19	54V	2.15	1.85 - 2.50	98 / 3.9	664 / 26.1	5	499 / 797.9
2283013	100/90-18	56V	MT2.50	2.15 - 2.75	108 / 4.3	642 / 25.3	5.6	516 / 825.2
2289013	100/90-19	57V	MT2.50	2.15 - 2.75	109 / 4.3	671 / 26.4	5.6	493 / 789.6
2289413	110/80-18	58V	MT2.50	2.15 - 3.00	111 / 4.4	640 / 25.2	5.6	517 / 827.8
2287013	110/90-18	61V	MT2.50	2.15 - 3.00	116 / 4.6	663 / 26.1	5.6	499 / 799.1
2288413	120/80-16	60V	MT2.75	2.50 - 3.00	126 / 5.0	601 / 23.7	5.6	551 / 881.5
2274813	120/80-17	61V	MT2.75	2.50 - 3.00	120 / 4.7	629 / 24.8	7.5	526 / 842.3
2278613	120/90-17	64V	MT2.75	2.50 - 3.00	128 / 5.0	649 / 25.6	7.5	510 / 816.3
2279213	140/80-17	69V	MT3.50	2.75 - 3.75	143 / 5.6	666 / 26.2	7.5	497 / 795.5

* Reinforced.

Equivalent MT90-16 = 130/90-16.

