

Roadrider: General purpose



- Ideal for mid-range bikes
- Large contact patch for excellent grip at all lean angles
- 150mph speed rating across the range



- Central tread groove to resist 'white-lining'
- Comprehensive range of sizes

When you rely on your bike as everyday transport, you want tyres that combine outstanding performance with long life; that's why you choose Avon's Roadrider. The Roadrider's rubber compound is specially formulated to give excellent roadholding year-round, while its carcass design provides a large 'footprint' at all lean angles. This tyre's high performance credentials are reinforced by the fact that all Roadriders are speed rated up to 150mph.

Another feature of the Roadrider that commuters in particular will appreciate is its central tread groove, designed to resist the 'white-lining' effect that can occur when riding over thickly applied road marker paint. A large range of sizes means that the Roadrider is ideal for a wide variety of bikes, including more traditional types.

Specification

Size	Load/Speed Index	Rec Rim (inch)	Alt Rim (inch) Min/Max	Overall Width (mm)	Overall Dia (mm)	Size	Load/Speed Index	Rec Rim (inch)	Alt Rim (inch) Min/Max	Overall Width (mm)	Overall Dia (mm)
ROADRIDER FRONT						ROADRIDER REAR					
3.25-19	54V	2.15	1.85 - 2.50	89	665	4.00-18	64V	2.50	2.15 - 3.00	108	671
90/90-18*	51V	2.15	1.85 - 2.50	90	619	120/80-17	61V	2.75	2.50 - 3.00	120	624
90/90-19*	52V	2.15	1.85 - 2.50	90	645	120/80-18	62V	2.75	2.50 - 3.00	120	649
90/90-21*	54V	2.15	1.85 - 2.50	90	695	120/90-17*	64V	2.75	2.50 - 3.00	119	648
100/80-17	52V	MT2.50	2.15 - 2.75	100	608	120/90-18	65V	2.75	2.50 - 3.00	119	673
100/90-16	54V	2.50	2.15 - 2.75	101	586	130/70-17	62V	3.50	3.00 - 4.00	130	614
110/70-17	54V	3.00	2.75 - 3.50	110	586G	130/70-18	63V	3.50	3.00 - 4.00	129	639
110/90-16	59V	2.50	2.15 - 3.00	109	604	130/70-18*	63V	3.50	3.00 - 4.00	129	639
110/80-17*	57V	2.50	2.15 - 3.00	109	608	130/80-17*	65V	3.00	2.50 - 3.50	129	640
120/70-17	58V	3.50	3.00 - 3.75	120	600	130/80-18	66V	2.75	2.50 - 3.50	129	665
* In preparation						130/90-17	68V	3.50	2.50 - 3.50	129	666
ROADRIDER UNIVERSAL						140/70-17	66V	3.75	3.50 - 4.50	140	628
100/90-18	56V	2.50	2.15 - 2.75	101	637	140/70-18	67V	3.75	3.00 - 4.50	139	653
100/90-19	57V	2.50	2.15 - 2.75	101	663	140/80-17	69V	3.50	2.75 - 3.75	142	656
110/80-18	58V	2.50	2.15 - 3.00	112	631	150/70-17*	69V	4.00	3.50 - 4.50	151	642
110/90-18	61V	2.50	2.15 - 3.00	109	655	150/70-18	70V	4.25	3.50 - 4.50	150	667
120/80-16	60V	2.75	2.50 - 3.00	120	598	150/80-16	71V	3.50	3.00 - 4.25	150	646
* In preparation						MT90-16*	74V	3.00	2.50 - 3.50	130	650

