

Viper Stryke: For high performance scooters



- Specially designed for modern scooters
- Exceptional tyre life
- Superb handling characteristics



Advances in scooter design mean that some modern machines are capable of speeds up to 100mph. To cope with the needs of these high performance scooters, Avon has produced the Viper Stryke, a tyre that combines sure-footed handling and agility with reassuringly long tyre life.

And in recognition of the fact that these bigger-engined scooters are often used for long distance commuting as well as nipping around town, the Viper Stryke is also comfortable to ride on and quiet. It's available in a range of sizes to fit many of the popular high performance scooters.

- Comfortable for long distance commuting
- Good value

Specification

Size	Load/Speed Index	Rec Rim (inch)	Alt Rim (inch) Min/Max	Overall Width (mm)	Overall Dia (mm)	Size	Load/Speed Index	Rec Rim (inch)	Alt Rim (inch) Min/Max	Overall Width (mm)	Overall Dia (mm)
------	------------------	----------------	------------------------	--------------------	------------------	------	------------------	----------------	------------------------	--------------------	------------------

AM63 FRONT

100/80-16	50P	2.50	2.15 - 2.75	100	566
110/70-16	52S	3.50	2.50 - 3.50	110	560
110/90-12	64P	2.50	2.15 - 3.00	110	503
110/90-13	56P	2.50	2.15 - 3.00	110	528
120/70-13	53P	3.50	2.75 - 3.75	120	498
120/70R14	55H	3.50	2.75 - 3.75	120	524
120/70-14	55S	3.50	2.75 - 3.75	120	524
120/70-15	56S	3.50	2.75 - 3.75	120	549
120/70R15	56H	3.50	2.75 - 3.75	120	549
120/80-14	58S	2.75	2.50 - 3.00	120	548

AM63 UNIVERSAL ORIENTATION

120/70-12	58P	3.50	2.75 - 3.75	120	473
130/70-12	62P	3.50	3.00 - 4.00	130	487
130/60-13	60P	3.50	3.00 - 4.00	130	486

AM63 REAR

120/80-16	60P	2.75	2.50 - 3.00	120	598
130/70-13	63P	3.50	3.00 - 4.00	130	512
140/60-13	63P	3.75	3.50 - 4.50	140	498
140/60-14	64S	3.75	3.50 - 4.50	140	524
140/70-12	65P	3.75	3.50 - 4.50	140	501
140/70-14	68S	3.75	3.50 - 4.50	140	552
140/70-16	65P	3.75	3.50 - 4.50	140	602
150/70-13	64S	4.25	3.50 - 4.50	150	540
150/70-14	66S	4.25	3.50 - 4.50	150	566
160/60R14	65H	4.50	3.75 - 5.00	160	568
160/60R15	67H	4.50	3.75 - 5.00	160	593

